



ITAL RESCUE

INTEGRITAS™ INTRINSICALLY SAFE LANTERN

XPR-5584GMX

NIGHTSTICK®

Life Depends on Light™

600
POWERFUL LUMENS
INCLUDING HIGH & LOW


NIGHTSTICK
INTEGRITAS 84



Rear green safety lights provide visibility in smoke filled applications



Powerful rare-earth tail magnets for additional hands-free use



Convenient locking snap-in charger included



Dustproof/Waterproof (IP-67) and chemical/heat resistant for any environment

**ATEX
ZONE 0**

**CLASS I
DIV 1**

FL 1 STANDARD	HIGH	LOW
	600 LUMENS	250 LUMENS
	13h	25h
	237m	167m
	14096cd	7007cd
	2m	
	1m	



600 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTEGRITAS™**LANTERN****LI-ION RECHARGEABLE****ITEM NUMBER/UPC**

XPR-5584GMX UPC# 0 17398807586

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- Charger meets requirements of NFPA-1901 (2009) Mounted in any Position
- CLASS I DIV 1: GRPS A-D T4
- CLASS II & III DIV 1: GRPS E-G T135°C
- CLASS I ZONE 0: AEx ia op is IIC T4 Ga
- ATEX Certification: II 1 G Ex ia op is IIC T4 Ga
- IECEx Certification: Ex ia op is IIC T4 Ga
- US Patent 9,713,217

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 600L, 13 hrs. runtime
- LOW: 250L, 25 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 14,096
- LOW: 7,007

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 237m
- LOW: 167m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.54 in / 19.2 cm
- WIDTH: 4.26 in / 10.8 cm
- DEPTH: 5.83 in / 14.8 cm
- WEIGHT: 2 lbs. 11 oz. / 1219 g

BATTERY

- Rechargeable Li-ion integrated battery pack

WARRANTY







- Limited lifetime warranty

PATENTED

- US PATENTS 9,713,217 & 10,879,519

WHAT'S INCLUDED

- Lantern w/ Integrated 5582-MAGNET Pad (preinstalled)
- Standard Rubber Pad
- Li-ion rechargeable battery pack
- Locking snap-in charger (5582-CHGR2)
- AC Charging Cord
- DC Charging Cord
- Removable shoulder strap (5580-STRAP)
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	600 LUMENS	250 LUMENS
	13h	25h
	237m	167m
	14096cd	7007cd
		
		

Bayco Products, Inc. XPR-5584GMX
640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
UL listed for use with Bayco Li-ion Battery Pack 5584-BATT



E 467756

ID 4003544

INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV 1 GRPS E-G T135°C
Ⓜ II 1 G Ex ia op is IIC T4 Ga
Ex ia op is IIC T4 Ga
DEMKO 19 ATEX 2254
IECEx UL 19.0075
-20°C ≤ Tamb ≤ +40°C
3.7V/Cell 5584-BATT
Um 10V

CE 2575

WARNING: Do not charge battery in a hazardous location
WARNING: Do not replace battery when an explosive
atmosphere is present.

SEE INSTRUCTION MANUAL
VOIR MANUEL

MFG MM-YY

CERTIFIED

**ITALRESCUE**